



Chicagoland Office Phone: 800-953-7626
Milwaukee Area Office Phone: 800-837-1700
Fax: 630-595-2386 Fax: 262-923-1797
E-mail: sales@lesman.com
Contact: _____ Ext. _____

Name: _____
Company: _____
Street: _____
City: _____ State: _____ Zip: _____
Phone: (____) _____ Fax: (____) _____
E-mail Address: _____
This is a: Request for Quote Order: PO# _____
Quantity Needed: _____ Date Required: ____/____/____
Shipping Method: _____ Partials Accepted: Yes No



Magnetic Flowmeter Application Datasheet



1. Detector Requirements

Environment

- General Purpose Nonhazardous Area
- Hazardous Area
- Submersible
- Sanitary Clean In Place? Yes No

Process Liquid _____

- Electrodes: 316L SS Hast C Zirconium Tantalum
 Platinum-Iridium Other _____

- Liner: PFA Polyurethane Rubber Chloroprene Ceramic

Process Conditions	Min.	Normal	Max.	Units
Temperature	_____	_____	_____	<input type="checkbox"/> °C <input type="checkbox"/> °F
Pressure	_____	_____	_____	<input type="checkbox"/> PSI <input type="checkbox"/> bar

Density _____ g/cm³ lb/ft³
(If specific gravity value is given, be sure to give reference temperature)

	Min.	Normal	Max.	Units
Viscosity	_____	_____	_____	_____
Flow Range	_____	_____	_____	_____

Process Pipe

- Nominal Pipe Diameter _____ In. cm.
Material _____
Pipe Lining? Yes No Material _____
Pulsating Flow? Yes No
Process Connections: DINPN ANSI (ANSIB16.5) Sanitary
Style: Wafer Flanged Flange Rating _____

2. Transmitter Requirements

Integral Only

Operating Modes

- Hart (Optional) DE
- Analog Foundation Fieldbus

Mounting Configuration:

- Integral Remote

Power Supply _____

Safety Approvals Required: _____

- Process Measurement Output(s): Standard
Contact Outputs: One Input and One Output 2 Inputs
Local Indicator: _____ Yes No
Corrosion-Resistant Coating Required: _____ Yes No
Watertight Glands Required: _____ Yes No

3. Other Application Details or Special Requirements

List any other information pertinent to model selection: _____

Configuration Datasheets

Lesman Value-Added Services

Index and Reference