



**SERIES 551**

**SPOOL VALVES**  
**1/4" NPT, Solenoid, Air or Manual/Mechanical Pilots**  
**Inline, Rail and Namur Mount**

**5/2**  
**5/3**

BODY ..... Light Alloy and Aluminum  
 INTERNALS ..... Stainless Steel, Alloy and Acetal  
 ENDCAPS ..... Polyamide  
 SEALS ..... BUNA N  
 FLOW ..... 0.9 Cv  
 MAXIMUM PRESSURE ..... 150 psi  
 MIN. PILOT PRESSURE ..... 35 psi



**Accessories:**  
 Rail Mounting

**INLINE 5/2**

<b>AIR</b>		
<b>Pilot</b>	<b>Pilot Return</b>	<b>Model Number</b>
Air	Spring	551 00 041
Air	Air	551 00 042

<b>Description</b>	<b>Model Number</b>
2 Station Rail	881 00 053
3 Station Rail	881 00 057
4 Station Rail	881 00 054
6 Station Rail	881 00 055
Mounting Feet (2)	881 00 049
Blanking Nut	881 00 056

**MANUAL/MECHANICAL**

<b>Pilot</b>	<b>Pilot Return</b>	<b>Model Number</b>
Roller Cam	Spring	551 00 032
Push	Pull	551 00 031
Pushbutton	Spring	551 00 033
Lever (detented)	Lever	551 00 026
Lever	Spring	551 00 027
Pedal	Pedal	551 00 028
Pedal	Spring	551 00 029

**SOLENOID**

<b>Pilot</b>	<b>Pilot Return</b>	<b>Model Number</b>
Solenoid	Spring	551 00 083
Solenoid	Solenoid	551 00 085

**INLINE 5/3**

**MANUAL**

<b>Pilot</b>	<b>Pilot Return</b>	<b>Model Number</b>	
		<b>Open Center</b>	<b>Closed Center</b>
Lever (detented)	Lever	551 00 035	551 00 034
Lever	Spring	551 00 036	551 00 030

**NAMUR MOUNT**

**NAMUR 5/2**

<b>Pilot</b>	<b>Pilot Return</b>	<b>Model Number</b>
Solenoid	Spring	551 00 106
Solenoid	Solenoid	551 00 108

Many other configurations available—consult factory  
 Solenoid pilots available in Type 4–4x, 7–9 and I.S.